

## Stenca Pipe

Pre-formed pipe sections with ceramic cloth facing:  
Technical Data:

Pipe sections Dimensions	Inside Diameter(D)	Outside Diameter(A)	Heat-resistance Maximum	Insulation Thickness	Length(L)
5mm	16.0mm	96.0mm	140 °C	40 mm	600 mm
3/4"	28.9mm	108.9mm	140 °C	40 mm	600 mm
1"	35.7mm	115.7mm	140 °C	40 mm	600 mm
1½"	50.3mm	130.3mm	140 °C	40 mm	600 mm
2"	62.3mm	142.3mm	140 °C	40 mm	600 mm
3"	90.9mm	170.9mm	140 °C	40 mm	600 mm
4"	116.3mm	196.3mm	140 °C	40 mm	600 mm
6"	170.3mm	250.3mm	140 °C	40 mm	600 mm

Additional pipe dimensions can be carried out according to order.



## Stenca Pipe

Pre-formed pipe sections without ceramic cloth facing:  
Technical Data:

Pipe sections Dimensions	Inside Diameter(D)	Outside Diameter(A)	Heat-resistance Maximum	Insulation Thickness	Length(L)
8"	223.1mm	303.1mm	140 °C	40 mm	600 mm
10"	277.0mm	357.0mm	140 °C	40 mm	600 mm
12"	325.9mm	405.9mm	140 °C	40 mm	600 mm
16"	410.4mm	490.4mm	140 °C	40 mm	600 mm
18"	461.2mm	541.2mm	140 °C	40 mm	600 mm
20"	512.0mm	592.0mm	140 °C	40 mm	600 mm
24"	613.6mm	693.6mm	140 °C	40 mm	600 mm

Foam bends above 6 inches are divided into 4 sections.  
After installation on pipe the rubber plating is fitted.  
Additional pipe dimensions can be carried out according to order.



LYD · VARME · KULDE